

## Overview:

DustMaster Water Carts suppress dust with effective, even spray distribution. Manually controlled fan spray valves deploy water while primary water cart functions are powered by our customer oriented remote control system. DustMaster design offers dedicated hydrant filling while supplied suction hose makes for easy filling from dams and other fill locations.

## Inclusions:

- Heavy Duty S.G 1.3 Cartage Tank (20 Year Warranty)
- UV Stabilised / Food Grade
- Safety Baffle Balls Fitted
- Forkable Gal Frame With Welded On Lifting Eyelets
- Loading Leg System With Swing Up Legs And Front Rollers
- Yanmar L100E 10.0Hp Electric Start Diesel Engine
- 2" or 3" High Pressure High Performance Tanker Pump
- 3 x Manual Valve Controlled Fan Sprays
- Pressure Relief Valve
- 30 Metre 1" Hose Reel With Nozzle
- Overhead Fill
- Hydrant Fill Point With Air Gap And One Way Valve
- Suction Fill Back through Pump 6m Hose And Foot Valve
- Individual Buttons For Each Spray And Beacon
- E Stop, And Lockable Battery Isolation
- Dribble Bar
- Remote Control For:
  - Engine On | Off
  - Spray Bar On | Off
  - Dribble Bar On | Off



Sizes to suit Tipper or Tray Trucks

Sizes to suit Tray Trucks  
Swing Leg Frames N/A

SLIP ON DIMENSIONS	7K	8K	10K	11K	12K	13K	13K LP	15K	18K
MAX LENGTH	3960	4180	4400	4400	4400	4400	4800	4800	6000
FOOTPRINT WIDTH	1750	1820	2030	1985	2030	2030	2080	2350	2350
MAX WIDTH	2200	2200	2200	2200	2200	2230	2300	2400	2400
HEIGHT	1570	1670	1770	2000	2000	2170	1960	2020	2020
TARE WEIGHT	1000kg	1100kg	1200kg	1250kg	1300kg	1350kg	1350kg	1440kg	2000kg

Suppressing dust with effective, even spray distribution.

Tank Size	LENGTH	WIDTH	FOOTPRINT WIDTH	HEIGHT
7K	3200	1900	1750	1570
8K	3300	2000	1820	1670
10K	3600	2100	2030	1770
11K	3600	2135	1985	2000
12K	3600	2200	2050	2000
13K	3700	2230	2030	2170
13K LOW PROFILE	3960	2280	2080	1960
15K	4300	2350	2350	2020
18K	5000	2350	2350	2020

## Performance and value

Featuring comprehensive equipment inclusions delivering great performance and value.